

Torque Wrench Pumps

Series : LTP



Electric Driven

- External adjustable torque settings pressure relief valve as standard.
- Maximum working pressure 700 Bar.
- In-built cooling system.
- Dual scale pressure gauge.
- Provides with auto retract function as standard.
- Motor ON/OFF control on pendant.
- Option for multi outlet ports.




Use Lifton LTH series twin hose assembly with double acting torque wrench and torque pump to ensure the integrity of your hydraulic system



Lifton torque pumps are also available with digital pressure gauges up on request. Add suffix "DG" with the pump model

number to order pump with digital pressure gauge



4 Outlet Valve Assembly (optional)

Drive	Model	Valve	Flow Rate (LPM)			Source of Power/ Capacity	Tank Capacity (Liter)	Dimension (LxBxH) mm	Weight (Kg)
			Low	Mid	High				
Electric	LTP1E	Single Outlet Elec. Solenoid Valve	4.5	-	0.5	220 V -50Hz / 1.1 Kw	1.5	340x165x330	12
Electric	LTP2E	Single Outlet Elec. Solenoid Valve	7	1.6	0.8	220 V -50Hz / 1.1 Kw	8	360x200x380	20
Electric	LTP4E	4 Outlet Elec. Solenoid Valve	7	1.6	0.8	220 V -50Hz / 1.1 Kw	8	300x375x458	25